

## Sewing Pattern — Chemise 5241

Recommendations on fabric: natural or mixed silk material  
150 cm in width.

You will also need: contrast fabric or bias binding for trimming.

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



### **CUTTING:**

#### Fabric:

1. Back – 2 pieces
2. Upper side front – 2 pieces
3. Centre front – 1 folded piece

#### Trimming:

4. Front facing – 1 piece
5. Armhole facing – 2 pieces
6. Loop – 2 pieces

### **INSTRUCTIONS:**

1. Stitch the centre back edges, press the seam to the left. Stitch the side and curves edges, leaving a slits open. Press the side seams backwards, press the curved seams open.

2. With right sides together, pin the facing to the garment along the top front edge. Stitch the facing 0,5 cm below the edge.

Flip the free edge of facing inside, over the top garment edge, and fold the facing raw edge the under to hide it. Topstitch on the right side to the previous seam.

3. Stitch the short raw edges of the armhole facings. Stitch the facing to the top edge of the garment making neck strap.

4. Press the slit seam allowances and the hem to the wrong side and topstitch 0,1 cm. above the foldline.
5. Make up loops, press them. Stitch the loops to the top back edge according to the marks.
6. Fit the chemise, place the shoulder straps into the loops, check the length and fix them.

**TECHNICAL DRAWING:**

