

Sewing Pattern — Dress 4199

Recommendations on fabric: stretch-knit fabric of natural or mixed fibers of two colors.

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam allowance: on hem of the dress – 2.0 cm. Other seam allowances – 0.7 cm

Attention! First of all, please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches, they must match up with corresponding pieces.



CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Advice:

Knit fabric pieces are sewn together with special stretch-stitch or narrow zig-zag stitch. Seam allowance on hem is stitched with twin needles to save stretchiness. Pieces can also be sewn together with 3 or 4 – thread serger. When serging, cut seam allowances to 0.6 – 0.8 cm.

Fabric 1:

1. Center back - cut 2
2. Center front – cut 1 on fold
3. Sleeve - cut 2

Fabric 2:

1. Side back - cut 2
2. Side front – cut 2
3. Neck Binding — cut 2
4. Cuff – cut 2

INSTRUCTIONS:

1. Sew side backs to center back and side fronts to center front. Serge seams and press toward side.
2. Sew and serge center back seam. Press seam toward left.
3. Sew sleeve into armhole. Serge.
4. Sew side edge together with sleeve edge.
5. Sew cuff into ring. Fold in half lengthwise and sew to bottom edge of sleeve. Serge seam.
6. Sew each neck binding short edges together to form a ring. Sew outer edge of both rings, right sides together. Clip into curves, turn right side out. Sew inner edge to neckline, binding seam should match up with center back seam. Topstitch just under binding/garment connecting seam.
7. Serge bottom edge of dress, press under, and topstitch.

TECHNICAL DRAWING: