

Sewing Pattern — Pants 5232

Recommendations on fabric: natural or synthetic silk.

You will also need: elastic lace tape; elastic tape; cotton jersey.

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Back – 1 folded piece
2. Front - 1 folded piece

Jersey:

3. Inside piece - 1 folded piece

Elastic lace tape:

4. Strip – 1 piece

INSTRUCTIONS:

1. With right sides together, stitch the front/back pieces . Stitch the jersey piece ride side to the back wrong side. Unfold the jersey piece to the front piece. Fold its seam allowance under and stew to the front piece with hand blind stitch.

2. Stitch the elastic tape with zigzag stitch to the leg openings 0,2 cm out from the edges stretching the elastic slightly. Fold the seam allowances to the wrong side of the garment and topstitch them with zigzag stitch (stretching slightly).

3. Topstitch the elastic lace strips to the lower edges of the pants wrong side to the right side.

TECHNICAL DRAWING:

