

## Sewing Pattern — Skirt 4198

Recommendations on fabric: natural or mixed woolen fabrics

You will also need: blind zipper, fusing, 1 button.

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: all seams - 1 cm, hem of the garment – 2 cm.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



### **CUTTING:**

#### Main fabric:

1. Front part – 1 folded detail
2. Back part – 2 details
3. Front basque – 1 folded detail
4. Back basque – 2 details
5. Belt – 1 detail

#### Fusing:

1. Belt – 1 detail

#### Lining:

1. Front part – 1 folded detail
2. Back part – 2 details
3. Front basque – 1 folded detail
4. Back basque – 2 details

## **INSTRUCTIONS:**

1. Apply fusing to belt.
2. Sew darts on front and back panels. Press depths towards center.
3. Sew side seams. Serge allowances and press onto back part.
4. Sew side seams of the basque and basque lining. Press apart the seam. Overstitch lower edge of the basque with lining. Turn basque onto right side and press. Make plaits and fix them along top edge.
5. Sew darts on lining. Press depths towards center. Sew middle edge of lining from zipper marker up to hem. Press the seam apart. Sew and serge side edges. Press seam allowances towards back part. Serge lower seam allowance of lining, turn inside and topstitch.
6. Fix upper edge of the skirt, basque and of lining of the skirt together.
7. Serge seam allowances of back part center edge and edge of the basque. Sew center edge from zipper marker up to hem. Press the seam apart. Sew zipper in.
8. Stitch belt to top edge of the skirt. Overstitch ends of the belt, slash seam allowances in corners and turn out. Turn inner edge of the belt inside and topstitch into connecting seam. Press ready belt.
9. Serge lower edge of the skirt, press onto wrong side and topstitch.
10. Mark and serge buttonhole (on the belt). Sew the button.

## **TECHNICAL DRAWING:**

