

## Sewing Pattern — Top 4196

Recommendations on fabric: thin blouse fabrics of natural or mixed fibers (cotton, viscose, polyester)

You will also need: fusing; elastic yarn; 6 buttons

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: on hem of the garment – 2 cm, along the edge of sleeve and on outer edge of flounces – 0 cm; all other seams – 1cm

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



### **CUTTING:**

#### Main fabric:

1. Back part - 2 details
2. Side front part - 2 details
3. Middle part of front part - 2 details
4. Central front part - 2 details
5. Sleeve – 2 details
6. Stand-up part of collar – 2 details
7. Buttonstand — 2 details
8. Flounce\_1 — 2 details
9. Flounce\_2 — 2 details

#### Fusing:

1. Stand-up part of collar – 1 detail
2. Buttonstand – 2 details

## **INSTRUCTIONS:**

1. Apply fusing to buttonstands and inner stand-up part of collar.
2. Fold details of stand-up collar right sides together and overstretch. Start and finish the stitch exactly near marked line of stand-up collar connecting seam. Slash seam allowances on rounded parts. Turn ready stand-up part of collar out and press.
3. Sew waist, shoulder and bust darts on back part and on side front part. Press depths of shoulder and waist darts towards center of corresponding details, press depths of bust darts upwards. Sew middle edge of back part, press seam onto left side and serge.
4. Serge with thin rolled seam outer sides of flounces. Sew central and middle parts of front part, inserting flounce\_1 between details. Press seam allowances onto central part, serge. Sew middle and side parts of front part, inserting flounce\_2 between details. Press seam allowances onto middle part, serge.
5. Serge outer edge of buttonstand. Fold buttonstand with central part of front part and overstretch edge of buttonstand. Slash seam allowances on rounded part, turn buttonstand onto wrong side, press, fix on neckline edge.
6. Sew side and shoulder edges, press seam onto back part and serge.
7. Sew upper stand-up part of collar into the neckline, turn open edge of lower stand-up collar and topstitch into upper stand-up collar connecting seam.
8. Put stitches on the sleeve according to markers with elastic yarn. Sew, press and serge edges of sleeves. Serge hem of sleeve with thin rolled seam. Sew sleeve into armhole. Press seam allowances and serge.
9. Press hem of the garment twice onto wrong side on 1 cm and topstitch.
10. Serge buttonholes on right front part, sew buttons on left front part.

## **TECHNICAL DRAWING:**

