

Sewing Pattern — Dress 5213

Recommendations on fabric: crepe-sateen of 150 cm width;
chiffon printed with flowers.

You will also need: fusible interfacing, decorative thin braid
with beads, dress zipper

If the pattern has double contour the seam allowances are
included. They are 1 cm unless specified otherwise.

If the pattern has single contour, the seam allowances are
NOT included and need to be added when laying out and
cutting details.

Seam allowances: 1 cm on all edges, 2 cm on central back
seam for sewing in zipper, 2 cm on hem.

Attention! First of all please print all the paper patterns and lay
them out at the width of fabric you plan to use (usually from
90 to 150 cm) to see how much fabric you will need. Don't
forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they
must coincide.



CUTTING:

(On the pattern pieces, “beam” means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as pleats etc. from the pattern onto your fabric.)

Crepe-sateen:

1. back bodice - cut 2
2. front bodice – cut 1 on fold
3. back skirt panel – cut 2
4. front skirt – cut 1 on fold

Chiffon:

1. back bodice – cut 1
2. front bodice – cut 1 on fold
3. back skirt – cut 2
4. front skirt – cut 1 on fold

Braid:

1. strap – cut 2

INSTRUCTIONS:

1. Apply interfacing strip of 2 cm width to wrong side of upper edges of bodice front/back and armhole edges.
2. Sew front/back darts in crepe-satin details and in chiffon details. Sew side seams. Lay chiffon bodice and crepe-satin bodice right sides together and sew them along upper edge. Trim seams and turn the bodice right side out. Baste the back center bodice and lining together close to edge.
3. Lay chiffon skirt panels on crepe-satin skirt panels and baste them together. Sew side seams, and back middle seam, leaving the opening for the zipper unstitched.
4. Sew skirt to bodice, right sides together. Press the seam upwards.
5. Press the seam opening for the zipper to wrong side.
6. Sew in zipper according to zipper instructions.
7. Press garment hem under and sew it by hand. Cut 2 straps from decorative braid. Sew front ends to front part according to marks. These will tie behind the neck. Sew braid also along dress upper edge.

TECHNICAL DRAWING:

