

Sewing Pattern — Dress 5212

Recommendations on fabric: lamé of 150 cm width; satin; chiffon

You will also need: lining, interfacing, thin decorative beaded braid, decorative flowers, dress length zipper.

Length from waist to hem is 110 cm.

If the pattern has double contour the seam allowances are included. They are 1 cm unless specified otherwise.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

(On the pattern pieces, “beam” means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as pleats etc. from the pattern onto your fabric.)

Lamé:

1. Back bodice – cut 2
2. Front bodice – cut 1 on fold
3. Back skirt panel – cut 2
4. Front skirt panel – cut 1 on fold

Satin:

3. Back skirt panel – cut 2
4. Front skirt panel – cut 1 on fold

Chiffon:

3. Back skirt panel – cut 2
4. Front skirt panel – cut 1 on fold

Lining:

1. Back bodice – cut 2
2. Front bodice – cut 1 on fold

3. Back skirt panel – cut 2

4. Front skirt panel – cut 1 on fold

Interfacing: Apply interfacing to wrong side of back and front lining pieces.

INSTRUCTIONS:

1. Sew front darts and side seams of bodice of both fabric and lining.

2. Lay lining on bodice, right sides together, and sew along edges of neckline and armholes; start and end stitch strictly on shoulder seam lines. Trim allowances close to seam; turn the garment right side out. Sew shoulder seams of fabric bodice. Turn lining shoulder edges under, place edge-to-edge and stitch.

3. Lay chiffon skirt panels, wrong side down, onto right side of lamé skirt panels; baste along edges; process as one skirt. Sew side seams and middle seams into front and back fabric and lining panels, leaving closure slit open. Gather the skirt waist along bodice lower edge; stitch correspondingly. Press waist seam allowance towards the bodice.

4. Press closure slit. Sew the zipper according to zipper instructions.

5. Sew the hem by hand, so that the lining hem is 2 cm shorter than the fabric one.

6. Sew decorative braid along neckline, waist seam and along the hem.

Sew decorative flowers to shoulder seams.

TECHNICAL DRAWING:

