

Sewing Pattern — Dress 5200

Recommendations on fabric: crepe-de-chine of 150 cm width

You will also need: organza; 1 zipper

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam Allowance: Hem 2.5 cm; all over seams 1 cm

Attention! First of all, please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches. They must match up with corresponding pieces.



CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Darts: The fold of the dart is always pressed toward the center of your garment, or down toward the hem.

Fabric:

1. Back – cut 2
2. Front – cut 1 on fold
5. Armhole bias binding – cut 2
6. Neckline bias binding – cut 2

Organza:

3. Front insert – cut 1 on fold
4. Back insert – cut 1 on fold

INSTRUCTIONS:

1. Sew front darts. Press toward hem. Sew center back seam.
2. Sew inserts to front and back, right sides together. Press seams towards the garment.
3. Sew left side seam from zipper notch to hem. Press seam apart, including opening for zipper. Sew in zipper. Sew right side seam. Press seam apart.
4. Press bias binding along the center, right sides out. Unfold, then fold edges to center, fold again along center. Trim dress upper edge allowance and armhole allowances to 0.5 cm. Insert upper edges into ready bias binding, and topstitch at 1 mm from lower fold.
5. Trim armholes with bias binding; begin at side seam, sew to back, make a strap, then continue sewing on front; stop at side seam.
6. Turn seam allowance of hem under, and topstitch.

TECHNICAL DRAWING:

