

## Sewing Pattern — Top 4194

Recommendations on fabric: two-side blouse fabrics of natural or mixed fibers (silk, viscose, mixed fabrics)

You will also need: fusible interfacing; invisible zipper  
If the pattern has a double line around it, the seam allowances are included.

**Note:** By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam Allowance: on hem of the garment – 2.0 cm, outer edges of the flounce – 0 cm, all other seams – 1cm.

Attention! First of all, please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches, they must match up with corresponding pieces.



### **CUTTING:**

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Darts: The fold of the dart is always pressed toward the center of your garment, or down toward the hem.

### **Main fabric:**

1. Back - cut 2
2. Left front - cut 1
3. Right front - cut 1
4. Sleeve – cut 4
5. Flounce – cut 1
6. Back neck facing - cut 1
7. Front neck facing - cut 1

### **INSTRUCTIONS:**

1. Sew darts on back. Press towards center. Sew center back seam. Serge and press toward left.
2. Sew dart on right front, press toward hem.
3. Serge flounce on side and outer side with narrow rolled seam. Sew left and right fronts, inserting flounce between them. Serge and press seam allowances towards center. Make pleats on top edge of flounce according to markers. Fold flounce at neck edge according to technical drawing and baste to neck edge.
4. Sew shoulder seams, serge and press seam toward back.
5. Sew side seams of the neck facings, press seam allowances apart. Serge outer edge. Pin the facing to garment, right sides together, and sew to neckline edge. Clip into curves, and understitch. Turn facing under. Topstitch.
6. Sew outer edge of sleeve, right sides together. Clip into curves, turn sleeve right side out, straighten seams, press. Sew sleeve to armhole, matching notches. Serge seam and press toward garment.
7. Serge separately left side edges. Sew left side seam, leaving an opening for zipper. Press left seam apart, including opening for zipper. Sew in zipper. Sew right side seam. Serge and press toward back. Tack seam allowance to armhole with 2 - 3 itches.
8. Serge bottom edge of garment. Press hem onto wrong side at 1 cm, then again at 1 cm and topstitch.

### **TECHNICAL DRAWING:**

