

## Sewing Pattern — Dress 5195

Recommendations on fabric: satin of 150 cm width, organza of 140 cm width

You will also need: fusing; zipper of 35 cm length; 3 buttons.  
If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



### **CUTTING:**

#### Fabric:

1. Middle back part – 2 pieces
2. Side back part – 2 pieces
3. Middle front part – 2 pieces
4. Side front part, one-piece with strap – 2 pieces
5. Front/strap facing – 2 pieces
6. Back facing – 2 pieces
7. Front skirt – 1 folded pieces
8. Back skirt – 2 pieces
9. Piping – 1 piece

#### Organza:

7. Front skirt – 1 folded piece
8. Back skirt – 2 pieces

Fusing: front/strap facing, back facing.

### **INSTRUCTIONS:**

1. Apply the fusing to wrong side of front/strap facing, back facing.
2. Stitch middle seam and relieve seams. Neaten allowances. Press middle seam leftwards, press relieves towards the center.
3. Stitch back relieve seams, middle seam up to closure slit. Neaten seams, press relieves towards

the center.

4. Stitch side seams, press them forward.

5. Make the narrowest roll of piping. Cut the roll into 3 parts and make button loops of them. Tack loops to edge of left strap (loop bendings must lay on the strap, loop ends lays on edge allowance). Loop size depends on button size.

6. Stitch middle edge into front facings, stitch back facings to them. Press seams apart. Lay the facing on the garment right sides together and stitch back upper edges between them and the zipper, as well as armhole edges, strap outer edges, front neckline. Cut allowances at 2-3 mm from stitch, cut strap ends diagonally. Slash neckline corners perpendicular to seam stopping 1 cm before the stitch. Fold facing into wrong side, neaten it and press.

7. Stitch fabric/organza skirt sides together. Lay under-skirt on fabric skirt with sides together, coincide side seams and process it as a single detail. Stitch middle seam between hem and closure mark. Make pleats along skirt upper edge. Stitch the skirt to dress upper part. Fold the seam upwards and neaten it.

8. Fold back facing upwards. Press closure allowances into wrong side. Stitch the zipper (teeth hidden). Fold the facing into wrong side and sew it to zipper braids.

9. Press hem allowance into wrong side? Fold it under and topstitch. Cut organza skirt so that it was 1.5-2.0 cm shorter than dress hem.

10. Sew buttons on right strap's end according to buttonholes.

### **TECHNICAL DRAWING:**

