

Sewing Pattern — Dress 5188

Recommendations on fabric: crepe-sateen of 150 cm width.

You will also need: lining; fusing; zipper.

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Back part – 2 pieces
2. Front side part – 2 pieces
3. Front part – 1 folded piece
4. Back panel – 2 pieces
5. Front panel – 1 folded piece

Trimming:

3. Collar – 4 pieces

Lining:

1. Back part – 2 pieces
2. Front side part – 2 pieces
3. Front – 1 folded piece
4. Back panel – 2 pieces
5. Front panel – 1 folded piece

INSTRUCTIONS:

1. Sew back details into fabric and lining.
2. Coincide collar details right sides together and overstretch along upper, front, lower and inner (from the mark to back middle seam) edges. Cease the allowance near the mark and turn the collar right side out.

3. Sew relieve front seams into fabric, inserting collar free lower edges. Sew frontrelieve seams into lining.
4. Sew fabric and lining details along edges.
5. Coincide lining and facing right side together and overstretch along upper edge. Turn the lining and topstitch it on seam allowance at 1-2 mm from stitch.
6. Coincide collar middle seam to back middle edge so that for a straight line, then fix with several stitches. Press back middle seam allowances into wrong side, apply the zipper under, and sew.
7. Sew side and middle edges of skirt (lining and fabric). Sew fabric skirt to fabric upper part; sew lining skirt to lining upper part. Press seam allowances apart, then sew fabric and lining together.
8. Fold the hem under so that lining hem is 2 cm shorter than this of fabric. Fix front seams close to the mark and collar corners with several stitches.

TECHNICAL DRAWING:

