

Sewing Pattern — Coat 5186

Recommendations on fabric: fabric of 150 cm width suitable for coats.

You will also need: lining; fusing; 5 buttons; raglan shoulder pads.

Seam allowances are provided if the pattern has double contour.

Seam allowances are NOT included if the pattern has single contour and need to be added when laying out and cutting details. All seams – 1.5 cm. Hem – 3 cm.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count double and symmetrical details.

When sewing the garment, pay attention to notches, they must coincide.

CUTTING:

Main fabric:

1. middle back part – 1 folded piece
2. middle front part – 2 pieces
3. side back part – 2 pieces
4. side front part – 2 pieces
5. front band – 2 pieces
6. hood – 4 pieces
7. back neckline facing – 1 folded piece
8. sacking – 2 pieces
9. front sleeve – 2 pieces
10. back sleeve – 2 pieces

lining:

1. back part – 1 folded piece (excluding neckline facing's width)
2. front part – 2 pieces (excluding front bands' width)
3. back sleeve – 2 pieces
4. front sleeve – 2 pieces

fusing: apply the fusing to wrong side of front bands, collar, back neckline facing, flaps. additionally: hem allowance.



INSTRUCTIONS:

1. stitch back relieves. make decorative stitch along back seams.
2. make diagonal slashes into front seam allowances and stitch lining sackings to pocket entrances into middle front parts. stitch middle front part to side front part and stitch sackings with the same seam. make decorative stitch along front part. tack sacking sides to front parts.
3. stitch shoulder seams and sleeves' upper seams.
4. stitch hood's middle seams. stitch inner hood into back/front necklines. stitch front bands'/back neckline facing's shoulder seams. stitch outer hood into front bands'/facing's neckline.
5. lay front bands on front parts right sides together and pin to front edgings, then pin together outer/inner collars' edges. topstitch the garment along front edgings and along hood edge. stitch pressed apart seams joining inner hood and back neckline facing together.
6. stitch sleeves' lower seams and coat's side seams. sew coat hem. sew front bands to coat hem.
7. sew sleeve hems.
8. sew shoulder pads.
9. stitch lining details. stitch the lining to sleeve hems, front bands' inner edges and back neckline facing. sew the lining under.
10. make buttonholes into right front edging.

TECHNICAL DRAWING:

