

Sewing Pattern — Pants 5178

Recommendations on fabric: silk of 150 cm width.

You will also need: fusing; 1 zipper; 1 button.

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Front part – 2 pieces
2. Back part – 2 pieces
3. Waistband – 1 piece
4. Button catch – 1 piece
5. Belt loop – 1 piece

Fusing: waistband, button catch.

INSTRUCTIONS:

1. Apply the fusing to wrong side of waistband and button catch.
2. Stitch darts, press darts' depth toward middle line.
3. Stitch side/instep seams. Neaten seam allowances and press them apart. Stitch middle front seam between closure mark and lower edge and stitch middle back seam with the same seam.
4. Press fly facing into wrong side as follows: at right edge press it along middle front line, at left part stop pressing 1 cm before front middle line (= closure allowance). Press button catch along the center right side out and neaten it along edges. Stitch the zipper under zip opening's left allowance, zipper's teeth meet the bending; lay button catch's bending to middle line so that neaten edge overlapped zipper braid. Pin zip opening's edges together coinciding middle front lines. Stitch zipper free braid to right fly facing; do not catch

fabric of front part. Topstitch right front part along closure catching the facing and folding button catch out. Stop stitching 1.5-2.0 cm before middle seam. Then fold button catch to its place and continue stitching up to the seam.

5. Press belt loop stripe's long allowances into wrong side. Press the stripe along the center, stitch long edges and topstitch the stripe along bending. Cut the stripe into 5 equal pieces. Tack belt loops to pants upper edge above front/back darts and above middle back seam.

6. Fold the waistband along the center wrong side out, overstitch ends, turn the detail right side out and press. Stitch the waistband to the garment right sides together; waistband's shaped end is on right side. Fold open edge under and topstitch along the seam joining the waistband.

7. Fold belt loops up, fold them under and topstitch to waistband upper edge.

8. Press hems into wrong side, fold edges under and sew by hand.

9. Make a buttonhole into right side, sew a button on left one.

TECHNICAL DRAWING:

