

## Sewing Pattern — Tunic 5176

Recommendations on fabric: jersey of 150 cm width.

You will also need: fusing.

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



### **CUTTING:**

#### Jersey:

1. Front part – 1 folded piece
2. Back part – 1 folded piece
3. Sleeve – 2 pieces
4. Back neckline facing – 1 folded piece
5. Front neckline facing – 1 folded piece
6. Pocket – 1 folded piece

Fusing: front/back neckline facing.

### **INSTRUCTIONS:**

1. Apply the fusing to wrong side of front/back neckline facings.
2. Stitch darts, shoulder/side seams, neaten them and press.
3. Stitch sleeve seams and neaten them. Stitch sleeves into armholes. Make two holes for ties into garment hem near the seam. 2 ties: 40 cm length and 3 cm width. Fold ties along the center wrong side out and overstretch them, turn right side out and press. Fold hem allowance into wrong side and topstitch. Pull ties in.
4. Stitch facing details together, neaten outer edge. Lay the facing on the garment right sides together and overstretch along neckline. Fold the facing into wrong side and topstitch the neckline.
5. Neaten hem allowance, fold in into wrong side and topstitch.

6. Fold pocket edges into wrong side and topstitch. Lay the pocket on the garment and topstitch along upper/lower edges. Make decorative stitch along pocket middle line. Make fixes at sides.

**TECHNICAL DRAWING:**

