

Sewing Pattern — Top 5174

Recommendations on fabric: silk of 150 cm width.

You will also need: 7 buttons.

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Middle front part – 2 pieces
2. Side front part – 2 pieces
3. Middle back part – 2 pieces
4. Side back part – 2 pieces
5. Strap facing – 2 pieces
6. Piping for upper back edge and armholes – 2 pieces
7. Piping for front neckline – 2 pieces

Fusing: one-piece front bands.

INSTRUCTIONS:

1. Apply the fusing to wrong side of one-piece front bands.
2. Stitch back middle/relieve seams. Neaten allowances. Press middle seam leftward, press relieves to middle line.
3. Stitch front relieves, neaten them and press toward middle line.
4. Stitch side seams, neaten them and press frontward.
5. Press hem allowance into wrong side, fold the edge under and topstitch with 1 cm seam.
6. Neaten front bands'/straps' straight edges. Fold front bands into right side and pin it. Pin

facings to straps right sides together.

7. Stitch pipings to trim upper edge. Press all the pipings along the center right side out. Lay pipings on garment's right side along corresponding edges: pipings' ends overlaps front bands and facings. Stitch facings, front bands and pipings, cut allowances, slash rounded seams, cut straps' corner bias close to seam.

8. Turn straps right side out, fold front bands and pipings into wrong side. Press edges. Make decorative topstitch of foot width along front edgings, neckline ties and back upper edge.

9. Make a pleat into each strap's right side, pin it and topstitch along bending.

10. Make buttonholes into right front edging, sew buttons on left one.

TECHNICAL DRAWING:

