

Sewing Pattern — Coat 5169

Recommendations on fabric: fabric of 150 cm width suitable for coats; trimming; lining of 150 cm width.

You will also need: fusing; raglan shoulder pads; 3 buttons for fly front; 2 decorative buttons.

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Middle back part – 2 pieces
2. Side back part – 2 pieces
3. Center front part – 2 pieces
4. Side front part – 2 pieces
5. Front band – 2 pieces
6. Back sleeve – 2 pieces
7. Front sleeve – 2 pieces
8. Back neckline facing – 1 folded piece
9. Outer collar – 1 folded piece
10. Inner collar – 1 folded piece
11. Pocket facing – 2 pieces
12. Inner cuff – 2 pieces
13. Outer cuff – 2 pieces

Lining:

14. Back part – 2 pieces
15. Front part – 2 pieces
16. Back sleeve – 2 pieces
17. Front sleeve – 2 pieces
18. Fly front – 2 pieces
19. Upper sacking – 2 pieces
20. Lower sacking – 2 pieces

Trimming:

21. Outer collar trimming – 1 folded piece

22. Cuff trimming – 2 pieces

Fusing: upper front/back parts, front bands, back neckline facing, collars and collar trimming, pocket facing, cuffs, cuff trimmings, upper sleeves.

INSTRUCTIONS:

1. Apply the fusing to wrong side of upper front/back parts, front bands, back neckline facing, collars and collar trimming, pocket facing, cuffs, cuff trimmings, upper sleeves.

2. Cut slit pockets with facings into front part: stitch neatly welts along short edges, turn them right side out and press. Topstitch bending along edges. Apply fusing stripe of 4 cm width on wrong side of front part (above pocket marking). Lay two pocket facings on front part right sides together; pin along pocket entrance marking and stitch (lengthwise edges of facings must coincide with middle line of pocket marking). Cut front part between stitches, diagonally at stitch ends. Do not cut through facing! Press seam allowances apart. Turn facings and sackings into wrong side through slit, then tack. Lay lower sacking on front part's wrong side on facing, with sacking upward, and topstitch the facing from right side catching the sacking. Press sacking downwards. Turn small triangle at slit ends into wrong side and stitch strictly to facings between upper stitch ends and lower stitch ends. Cut sackings, adjust them and stitch together. Topstitch the facing on front part along short sides.

3. Stitch middle back seam/back relieves and press them apart.

4. Stitch front/back sleeves to front/back parts correspondingly, press seams apart

5. Stitch sleeves upper seams. Stitch sleeve lower seams and coat's side seams with one seam.

6. Make fly front on right front edging: Lay two linings for fly front on front band right sides together. Pin as directed along marked closure, then stitch (NB! Facings' long edges must coincide closure marking's middle line) Cut front band between stitches, diagonally at stitch ends. Do not cut through lining! Press seam allowances apart. Turn linings into wrong side through slit to make neat frame, then tack. On right side: topstitch lower lining on joining seam. Press the lining downward. Turn small triangle at slit ends into wrong side and stitch strictly to lining between upper stitch ends and lower stitch ends. Make buttonholes into front band catching lower lining. Fix both lining to front band making stitches between buttonholes perpendicularly to front edging.

7. Stitch cuff trimming to outer cuff, press seams apart. Stitch outer/inner cuffs' short edges, lay them right sides together and overstitch along upper edge. Stitch inner cuff to sleeve. Press the seam apart.

8. Stitch collar trimming to outer collar.

9. Stitch inner collar into neckline. Stitch shoulder seams of back neckline facing and front bands, stitch outer collar into facing's/front bands' neckline. Press allowances apart, slash at roundings.

10. Lay outer collar joint with front bands on the garment (right sides together), overstitch edgings and the collar; turn right side out and press. Fix seams joining collars together. Tack

front edging and the collar.

11. The hem: lay front bands frontward. Fold hem allowances into wrong side and sew. Fold front bands into wrong side.

12. Sew shoulder pads.

13. Stitch lining details. Fold lining hem so that it was 2 cm shorter than garment hem. Lay the lining on the garment right sides together and stitch the lining to inner edges of front bands and to back neckline facing folding garment's hem out. Turn the coat right side out.

14. Sew the lining to garment hem and to outer cuff at sleeves.

15. Make a buttonhole into right front edging, sew the button accordingly.

TECHNICAL DRAWING:

