

## Sewing Pattern — Blouse 5167

Recommendations on fabric: linen/cotton/silk/viscose of 150 cm width

You will also need: fusing; 7 buttons.

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



### **CUTTING:**

Fabric:

1. Front part cut out with inner collar – 2 pieces
2. Back part – 2 pieces
3. Front band cut out with outer collar – 2 pieces
4. Front sleeve – 2 pieces
5. Back sleeve – 2 pieces

Fusing: front bands cut out with outer collar.

### **INSTRUCTIONS:**

1. Apply the fusing to wrong side of front bands cut out with outer collar.
2. Stitch front/back darts, stitch middle back seam.
3. Stitch shoulder seams, slash into corners at collar's beginning.
4. Lay front parts right sides together and stitch collar edge.
5. Stitch the collar into the neckline between corners.
6. Stitch collar's middle edge at front band. Neaten front bands' inner edges up to shoulder edges. Overstitch front part with front bands.



7. Slash front band's allowance into corner up to seam line. Turn the collar right side out, fold front bands into wrong side. Press edges. Fold outer collar's open edge and topstitch along the seam joining inner collar. Fix front bands on shoulder seams.

8. Stitch side seams.

9. Stitch sleeve front/outside seams.

10. Stitch sleeves into armholes easing along sleeve caps.

11. Turn blouse/sleeve hems into wrong side and topstitch along edges.

12. Make buttonholes into right front edging, sew buttons on the left one.

**TECHNICAL DRAWING:**

