

Sewing Pattern — Skirt 5151

Recommendations on fabric: combined or natural fabric of 150 cm width

You will also need: fusing; 1 zipper.

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Back panel - 1 folded detail
2. Front panel - 1 folded detail
3. Front panel yoke - 1 folded detail
4. Back panel yoke - 1 folded detail
5. Belt loop - 4 details

Fusing: yoke lower details.

INSTRUCTIONS:

1. Strengthen yoke lower parts with fusing.
2. Sew lower edges of yokes to upper edges of panels, press allowances into yokes.
3. Sew right side seam from zipper mark down to slit mark, press allowances apart. Tack zipper under split edge, sew on the right side.
4. Sew side seams of lower yokes.
5. Work the upper edges of skirt with yokes, topstitch allowances on, trim and press. Topstitch open edges of lower yokes into upper ones joining seam. Tuck lower edges of yokes and sew to zipper band.

6. Topstitch cutting into panels allowances along the marking.
7. Turn over hem allowance, press, then topstitch.
8. Sew lengthwise edges of belt loops, tuck and press. Topstitch belt loops ends on the yokes in according with marking.

TECHNICAL DRAWING:

