

Sewing Pattern — Trousers 5148

Recommendations on fabric: natural or mixed silk of 150 cm width

You will also need: 1 zipper of 18 cm length

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Front part – 2 pieces
2. Back part – 2 pieces
3. Front facing – 1 folded piece
4. Back part facing – 2 pieces

INSTRUCTIONS:

1. Sew darts, then press darts depths toward the center.
2. Sew side seams, with a zipper slit in the left seam left. Sew leg inside seams. Press allowances apart. Sew front middle seam and back middle one with one stitch. Press the allowances downward the roundings.
3. ZIPPER: Press slit edges allowance into wrong side. Sew the zipper under slit edges.
4. Garment upper edge: sew back middle seam and right side one. Topstitch facing on parts upper edges right sides together. Cut the allowances to 0.5 cm width, place them under facings and stitch along the edges. Turn facings into wrong side, press the upper edge. Turn the facings from inside, sew them on zipper braid. Additionally, sew facing lower edges to seam allowances and darts depths.
5. Turn the hem allowance under, then sew.

TECHNICAL DRAWING:

