

Sewing Pattern — Top 5143

Recommendations on fabric: elastic or knitted fabric of 150 cm width.

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

- 1 Front part – 1 folded piece
- 2 Back part – 2 pieces
- 3 Back strap – 1 folded piece
- 4. Back facing – 1 folded piece

Fusing: back strap, back facing.

INSTRUCTIONS:

1. Apply the fusing to wrong side of back strap and back facing.
2. Sew back middle seam and back darts. Press back darts towards back part center.
3. Turn one-piece facing of upper front part to right side and topstitch along armhole edges.
4. Stitch the strap along lengthwise edge wrong side out, then turn right side out and press, stretch slightly along bending.
5. Turn one-piece facings of upper front part and armhole allowances to wrong side. Insert strap ends into upper corners between allowances. Topstitch the garment on right side along armholes at 0.7 cm from edge.

6. Sew back facing to back part along upper edge, right sides together. Topstitch allowance on facing.
7. Sew side seams (do not catch facing). Sew facing to allowance of middle/side seams and darts depths.
8. Fold the hem under and topstitch at 0.7 cm from edge.

TECHNICAL DRAWING:

