

Sewing Pattern — Trousers 5140

Recommendations on fabric: natural or mixed with lycra fabric of 150 cm width

You will also need: 1 zipper of 22 cm length.

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Front part – 2 pieces
2. Back part – 2 pieces
3. Front facing – 2 pieces
4. Back facing – 2 folded pieces
5. Pocket – 2 pieces

Fusing: facing details.

INSTRUCTIONS:

1. Apply the fusing to wrong side of facing details.
2. Sew darts, press darts towards the center.
3. Topstitch pockets on the front parts of the garment.
4. Sew side seams. Sew step seams. Press allowances apart. Sew front middle seam and back middle one with one stitch, leave a slit for the zipper. Press the allowances downward the roundings.
5. ZIPPER: press slit edge allowances into wrong side. Topstitch the zipper on slit both edges.

6. Garment upper edge: sew facings along side edges. Topstitch the facing on parts upper edges right sides together. Cut the allowances to 0.5 cm width, place them under facings and stitch along the edges. Turn facings into wrong side, press the upper edge. Turn the facings from inside, sew them on zipper braid. Additionally, sew facing lower edges to seam allowances and darts depths.

7. Turn the hem allowance under, then sew.

TECHNICAL DRAWING:

