

Sewing Pattern — Trousers 5138

Recommendations on fabric: mixed/nature fabric suitable for suits of 150 cm width

You will also need: 1 zipper of 22 cm length; 1 button

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Front part – 2 pieces
2. Back part – 2 pieces
3. Button catch – 1 piece
4. Belt loop – 7 pieces
5. Waistband – 1 piece
6. Front side part – 2 pieces

Fusing: waistband

Lining:

1. Lower sacking – 2 pieces
2. Upper sacking – 2 pieces
3. Front part – 2 pieces

INSTRUCTIONS:

1. Apply the fusing to wrong side of waistband.
2. Sew darts, press the dart depths towards middle seams of parts.
3. Sew upper sacking and front part right sides together, then sew it along the pocket entrance. Turn the sacking into wrong side, then topstitch the front part along pocket entrance. Topstitch the folded-ender front side part edge on the sacking upper edge.
Pin the front part on the front side part.
Sew sacking edges from wrong side.
4. Sew the lining and the front part wrong sides together along all edges excepting lower one, catching sacking side and upper allowances.
5. Fold front parts right sides together. Under the notch mark, sew front middle seam. Stop sewing 2 cm before inside leg seam.
6. ZIPPER: press zipper closure one-piece allowance into wrong side. Sew the zipper under the closure allowance edge (left edge) along the edge. Sew zipper free braid to right edge to one-piece facing. Fold the button catch along the center, stitch it to upper and lower short edges. Topstitch the zipper closure one-piece facing on the button catch on the garment left part. Topstitch the slit right edge catching the facing.
7. Fold one front and one back parts right sides together. Sew side seams to the notch mark. Blank the hem. Sew step seam. Press seam allowances apart.
Turn the hem allowance into right side, then stitch along slit edges. Turn it, press, then topstitch the hem on the garment along marking.
8. Sew the back edge and front edge unsewn part with one seam. Press the allowances apart to the roundings.
9. Blank the belt loops along the straight and one of short ends.
10. Sew one of waistband lengthwise edges and garment upper edge, right sides together. Leave the closure projecting allowance on the left edge.
Insert belt loops raw ends between the waistband and the garment.
Press the joining seam allowances toward the waistband. Fold the waistband along the center, sew front ends. Turn the waistband right side out. Topstitch strictly along joining seam on right side. Topstitch belt loops ready ends on the waistband.
11. Turn hem allowance into wrong side, then sew.
12. Make a buttonhole into waistband right end. Sew the button on the left one.

TECHNICAL DRAWING:

