

Sewing Pattern — Roll-neck 4188

Recommendations on fabric: medium to high stretch-knit fabric of natural/mixed fibers.

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam allowance: hem and lower edge of sleeve – 1.5 cm, all other seams - 1 cm

Attention! First of all, please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches. They must match up with corresponding pieces.



CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Advice:

Knit fabric pieces are sewn together with special stretch-stitch or narrow zig-zag stitch. Seam allowance on hem is stitched with twin needles to save stretchiness. Pieces can also be sewn together with 3 or 4 – thread serger. When serging, cut seam allowances to 0.6 – 0.8 cm.

Fabric:

1. Back – cut 1
2. Front – cut 1
3. Sleeve – cut 2
4. Neckband (collar) – cut 1

*Note: Test neckband before sewing, to make sure it will fit over your head. Adjust length if needed.

INSTRUCTIONS:

1. Sew shoulder and side seams of back and of front. Serge and press seams toward back.
2. Sew sleeve seams. Serge and press seams.
3. Sew sleeve into armhole, matching notches. Serge and press seams.
4. Serge lower edges of garment and sleeve. Turn onto wrong side, press and topstitch.
5. Sew neckband into ring. Fold collar in half, wrong sides together. Sew neckband to neckline, matching notches. Collar seam is near left shoulder seam. Serge and press collar connecting seam.

TECHNICAL DRAWING:

