

Sewing Pattern — Skirt 5135

Recommendations on fabric: fabric suitable for skirt, e.g. crepe sateen.

You will also need: 1 skirt zipper, 1 button.

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Seam allowances: All seams 1 cm, 2 cm for hem

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

(On the pattern pieces, “beam” means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as pleats etc. from the pattern onto your fabric.)

Fabric:

1. skirt panel – cut 4
2. waistband – cut 1 of fabric and 1 of fusible interfacing

INSTRUCTIONS:

1. Apply fusible interfacing to waistband.
2. Sew back center seam from bottom of zipper mark. Sew front center seam and side seams. Press seam allowances open, including opening for zipper.
3. Sew in zipper according to zipper instructions.
4. Pin waistband to skirt making sure that notches match. Sew waistband to waistline edge, right sides together. The center back left seam allowance should line up with the lapped zipper and the center back right side should extend enough so that the left side can overlap. Press the seam allowance of the unstitched long edge toward the wrong side.

5. Fold waistband along center line at the ends, right sides together and sew short ends. Trim corners. Pull corners out so they are square.
6. Press seam toward waistband. Trim and grade seams as needed. Press along center line so that waistband-facing is toward inside and turned edge meets up with the edge of the seamline. Slip-stitch in place. Top-stitch along edges of the outside waistband if desired.
7. Turn up hem allowance along hemline up to 2 cm width, press, then topstitch. Or hem as desired.
8. Work a buttonhole into the left end of waistband and sew the button to the right.

TECHNICAL DRAWING:

