

Sewing Pattern — Skirt 5122

Recommendations on fabric: light-weight, well draping fabric / crepe.

You will also need: skirt zipper

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam allowance: 1 cm

Attention! First of all, please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches, they must match up with corresponding pieces.



CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Fabric 1:

1. Front- cut 1
2. Back - cut 1
3. Front facing - cut 1
4. Back facing - cut 1

INSTRUCTIONS:

1. Sew left side seam from zipper end mark to hem. Press seam allowances apart including opening for zipper. Sew in zipper.
2. Sew right side seam and seam on facings.
3. Pin facing to skirt, right sides together, and sew to top edge of skirt. Clip into curves and understitch. Turn ends of facing inside. Turn facing under and slipstitch to zipper tape and to allowances of side seams.
4. Serge bottom edge of skirt, press seam allowance under, topstitch close to folded edge, then on wrong side, cut off seam allowance close to stitch. Or, depending on the fabric used, finish hem as desired.

TECHNICAL DRAWING: