

Sewing Pattern — Blouse 5114

Recommendations on fabric: light blouse fabrics/batiste of 140 cm width

You will also need: fusing; 5 buttons.

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Central back part - 1 folded detail
2. Side back part - 2 details
3. Side part of the front - 2 details
4. Central part of the front - 2 details
5. Sleeve - 2 details
6. Cuff of sleeve - 2 details
7. Collar - 2 details

Fusing: one-piece buttonstand and cuff. Press fusing only to one detail of collar.

INSTRUCTIONS:

1. Apply fusing to wrong side of one-piece buttonstand, cuff and lower collar.
2. Sew princess seams of front part and of back part. Serge seam allowances and press apart.
3. Sew side and shoulder seams. Turn seam allowance on hem at 1, 5 cm and topstitch.
4. Stitch collar along outer contour and, taking open edges together, sew into the neckline.
5. Turn one-piece buttonstands onto right side and stitch to neckline edge on top of collar. Sew collar into the neckline of back part from buttonstands' ends. Turn buttonstands onto wrong side, sew to lower edge of the blouse.
6. Sew sleeves seams. Serge seam allowances and press apart.

7. Ease each sleeve in on rounded part between notches. To do that put loose machine stitch on both sides of sleeve connecting seam marked line, slightly gather the fabric on lower thread. Fold sleeve with the garment right sided touching and pin into armhole, first only into lower part, aligning sleeve seam with side seam and cross marker on the front and on sleeve. Do not ease in armhole or sleeve! Pin sleeve above shoulder seam of the blouse, aligning cross marker with the seam on rounded part. Then pin the sleeve into upper part of the armhole, easing it in evenly. Tack the sleeve and sew it in from side of sleeve, starting the stitch near seam of sleeve. Serge seam allowances together. Press seam allowances onto sleeve on rounded part.
8. Fold cuff in half lengthwise and stitch on short edges. Stitch outer half of cuff to lower edge of sleeve, turn inner half and sew above connecting seam.
9. Serge 5 buttonholes along buttonstand of right front part sew buttons on left front part.

TECHNICAL DRAWING:

