

## Sewing Pattern — Dress 5112

Recommendations on fabric: jeans fabric

You will also need: fusing, 7 buttons

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



### **CUTTING:**

Main fabric:

1. Front part - 2 details
2. Back part - 2 details
3. Back neckline facing - 1 detail on fold
4. Collar - 2 details on fold
5. Sleeve - 2 details

Fusing: apply fusing to one-piece buttonstands, back neckline facing and one detail of collar (= top collar).

### **INSTRUCTIONS:**

1. Sew darts crosswise on front parts, bringing slowly to null. Tie in knots the threads at the ends of darts. Press depths of the darts downwards.
2. Make and pit pleats on wrong side of front and back parts, exactly leveling the marking. Sew between cross notches. Press the pleats in direction to corresponding center lines; from the right side stitch into the edge and at 0,5 cm, stitching across on top and lower ends of pleats by that.
3. Sew center back seam and side seams above slits' notches, sew shoulder seams, press seam allowances apart.
4. Fold collar details right sides together, curve outer edges a bit out and pin together, so top collar gets a "length ease" to look more attractive on ready garment. Sew along outer contour, leaving collar connecting seam open. Cut seam allowances to 0,5 cm, cut off crosswise in corners. Turn collar out, pull carefully the corners of collar out with the needle. Stitch up along

outer edge into the edge and at 0,5 cm, catching lower collar. Tack together open edges of collar, sew into the neckline from the right side. Cross notch is aligned with shoulder seam, front edges of collar are on on center line on front parts.

5. Front bands and neckline: stitch back neckline facing with its right side to right side of one-piece buttonstands. Press seam allowances apart. Stitch facings and buttonstands right sides together to the neckline edges, exactly aligning shoulder seams on the dress and buttonstands with facing. Cut allowances of connecting seam up to 0, 5 wide. Turn buttonstands and the facing onto wrong side. Serge bands and the neckline.

6. Lower edge and side slits: press onto wrong side first hem seam allowances, then seam allowances along side slits. In corners of lower edge turn crosswise seam allowances along the slits. Stitch up lower edge and edges of slits from the right side at 1.2 cm.

7. Stitch up bands and collar connecting seam sewing from the right side into the edge. Sew buttonstands by hand to allowances on hem and to shoulder seam allowances.

8. Sew seams of sleeves. Press seam allowances apart. Press seam allowances of lower edge of sleeves onto wrong side, stitch up from the right side.

9. Sew in the sleeves: pin the sleeve into the armhole right sides together, leveling notches. Tack the sleeves in and sew them in. Connect seam allowances and serge.

10. Make buttonholes along right buttonstand. Sew on buttons along front part's center line on the left front part.

#### **TECHNICAL DRAWING:**

