

## Sewing Pattern — Pants 5099

Recommendations on fabric: silk fabric (light well shaping fabrics), width 90cm

You will also need: lining, width 140 cm; fusing; 1 zipper of 20 cm long

If you are planning to use non-transparent fabric, you don't need lining

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



### **CUTTING:**

#### Fabric:

1. Front half - 2 details
2. Back half - 2 details
3. Front belt - 1 folded detail
4. Back belt - 1 folded detail

Lining: front half, back half – up to lining line, front belt, back belt.

Fusing: front and back lining belt

### **INSTRUCTIONS:**

1. Apply fusing to front and back belt from lining. Sew darts on back panels, press depths to middle seam line.
2. Sew side seams, ending the stitch at approx. 5 cm above lower slit cross marker. Leave a slit in upper part of left side seam open for zipper.
3. Sew leg edges.
4. Put halves of trousers one into another right sides together and sew front and back middle seams with one stitch.
5. Sew right side seam on outer details of the silk belt. Stitch outer belt to top edge of trousers, press seam allowances onto belt.

6. Tack zipper under edge of top slit in left side seam up to top edge of the belt so that zipper blade can not be seen, and stitch by 0, 5 cm. Turn seam allowances on hem of pants halves onto right side and stitch along edges of lower side cuts up to cross markers.
7. Turn seam allowance on hem top edge of each pants half downwards and pin. Sew open section of side seam up to marker slit. Turn hem onto wrong side. Press lower edge off pants and slit edges. Sew hem.
8. Sew darts on lining details and sew seams. Stitch lining belt to top edge of lining. Press seam allowances apart.
9. Put lining belt (inner belt) right side onto right side of the belt of pants, do not insert lining into pants by doing this. Sew top edges of outer and inner belts. Turn belt out, insert lining into pants, wrong side to wrong side, turn and sew to zipper tapes. Put the stitch from right side of pants exactly into connecting seam of the belt, catching lining.
10. Turn hem of lining.
11. Press creases.

**TECHNICAL DRAWING:**

