

## Sewing Pattern — Skirt 5092

Recommendations on fabric: wool crepe of 150 cm width

You will also need: lining; fusing; 3 buttons.

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



### **CUTTING:**

Fabric:

1. Front panel - 2 details
2. Back panel - 1 folded detail

Lining: front panels (excluding facing width) and back panel.

Fusing: strengthen one-piece facings of front panels with fusing. Press additionally fusing stripe of 0.5 cm width along waistline (cut stripes in accordingly to waistline shape).

### **INSTRUCTIONS:**

1. Sew side seams into fabric and lining.
2. Turn one-piece facing into right side, sew lining to facing edges. Do not sew 10 cm from the lower edge.
3. Fold lining and facings into wrong side.
4. Undersew the skirt. Undersew the lining so that the lining was 2 cm shorter than fabric skirt. Sew open seams of the lining. Sew facings to hem edge.
5. Work button holes according to marking into front panels upper corners. Sew buttons correspondingly to button holes. Sew the third button as decorative according to marking.

**TECHNICAL DRAWING:**

