

## Sewing Pattern — Skirt 5088

Recommendations on fabric: wool or semi-wool, bottom weight fabric.

You will also need: lining, fusible interfacing, 1 zipper 20 cm length, 1 button.

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: 1 cm on all edges. Hem – 2 cm.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



### **CUTTING:**

(On the pattern pieces, “beam” means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.)

#### Fabric:

1. Front panel – cut 1 on fold
2. Back panel -cut 2
3. Waistband – cut 1 and cut 1 of fusible interfacing

#### Lining:

1. Front panel – cut 1 on fold
2. Back panel – cut 2

## **INSTRUCTIONS:**

1. Apply fusible interfacing to waistband.
2. Sew back center seam between notches. Press seam open, including opening for zipper.
3. Sew in zipper according to zipper instructions.
4. Sew darts and side seams.
5. Sew darts and seams of lining. Leave an opening for the zipper and the skirt slit.
6. Place lining into skirt, wrong sides together and baste at the waist. Slip-stitch zipper opening in lining along zipper tape on inside of skirt.
7. Sew waistband to waistline edge, right sides together. The center back left seam allowance should line up with the lapped zipper and the center back right side should extend enough so that the left side can overlap. Press the seam allowance of the unstitched long edge toward the wrong side.
8. Fold waistband along center line at the ends, right sides together and sew short ends. Trim corners. Pull corners out so they are square.
9. Press seam toward waistband. Trim and grade seams as needed. Press along center line so that waistband-facing is toward inside and turned edge meets up with the edge of the seamline. Slip-stitch in place. Top-stitch along edges of the outside waistband if desired.
10. Hem the skirt. Hem the lining 2 cm shorter than the skirt.
11. Slip-stitch the skirt slit seam allowance to the inside over the lining slit opening.

## **TECHNICAL DRAWING:**

