

Sewing Pattern — Skirt 5084

Recommendations on fabric: light woolen or mixed fabrics (crepe, gabardine)

You will also need: lining; fusible interfacing; elastic- 3 cm wide; skirt zipper; 1 button

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam Allowance: hem 3 cm, all other seams 1 cm

Attention! First of all, please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches. They must match up with corresponding pieces.



CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Darts: The fold of the dart is always pressed toward the center of your garment, or down toward the hem.

Fabric:

1. Front - cut 1
2. Back -cut 2
3. Waistband (belt) - cut 1
4. Belt loop - cut 1

Lining: front and back panels excluding the width of vent facing and hem allowance

Fusible interfacing: self-facings of the vent and waistband except for sections for elastic.

INSTRUCTIONS:

1. Sew darts on front and back skirt, press towards center.
2. Sew center back seam from zipper mark to vent. Press seam apart including opening for zipper. Sew in zipper. Sew side seams, press seams apart.

3. Press hem seam allowance onto wrong side and hand stitch or topstitch.
4. Press vent facing onto wrong side and sew to hem. Sew vent seam allowance on right side. Sew left back from the end of the vent at 5 cm upwards and then diagonally to center seam.
5. Sew lining same as main fabric. Press seam allowance for zipper onto wrong side. Pin lining to skirt, wrong sides touching, baste top edges.
6. Press long sides of belt loop strip at 0.75 cm inside, sew the strip together along the edge, cut into 4 equal parts. Tack belt loops to darts along top edge of the skirt.
7. Pin the waistband to the top edge of the skirt, right sides together and sew, leaving right end for closure extended for button. Sew ends of the waistband. For elastic sections, sew the waistband along connecting seam between darts.
8. Cut elastic in 2 pieces, insert between darts and sew to the waistband, continuing the line of each dart, regulating needed length. Fold and then topstitch inner seam allowance of the waistband into connecting seam. Sew the waistband in the center of each elastic section between cross stitches, stretching the elastic.
9. Turn under short sides of the belt loops and sew to top edge of the waistband. Make a buttonhole on left side of the waistband, sew a button on right side.
10. Hem the lining 2 cm shorter than the skirt, turn edges of the lining vent onto wrong side and topstitch.

TECHNICAL DRAWING:

