

Sewing Pattern — Raincoat 4182

Recommendations on fabric: natural or mixed whipcord

You will also need: fusible interfacing; 4 buttons; lining; shoulder pads

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam allowance: all seams - 1 cm; hem of the garment - 3.5 cm; edges of pocket bags and off-set welt — 2 cm

Attention! First of all, please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches. They must match up with corresponding pieces.



CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Darts: The fold of the dart is always pressed toward the center of your garment, or down toward the hem.

Main fabric:

1. Front – cut 2
2. Back – cut 1
3. Upper sleeve – cut 2
4. Lower sleeve – cut 2
5. Front band facing – cut 2
6. Facing of sleeve – cut 2
7. Off-set welt – cut 2
8. Back neck facing – cut 1
9. Collar – cut 2
10. Belt – cut 1
11. Big pocket bag – cut 2

Lining:

1. Front – cut 2
2. Back – cut 1
3. Sleeve – cut 2
4. Small pocket bag – cut 2

*ATTENTION: Front and back lining pieces are cut using main fabric patterns excluding width of front band facing and back neck facing correspondingly.

Fusible interfacing: front band facing, off-set welt, back neck facing, outer collar

INSTRUCTIONS:

Attention: Side edges of the garment are serged from waistline up to hem.

1. Apply interfacing to front band facing, back neck facing, outer collar, edge of the armhole on front and on back. Apply interfacing to pocket entrance on front. Apply fusible bias tape of 1 cm wide on front along lapel fold line.
2. Sew and press the darts towards center on back. Sew and press darts on front.
3. Mark pocket place. Press off-set welt in half lengthwise, wrong sides together. Topstitch small pocket bag onto inner side of off-set welt. Stitch off-set welt to front along lower line of pocket marking. Sew big pocket bag to front along top line of pocket marking. Finish the stitches near short lines of marking. Cut open the pocket entrance. Make diagonal snips at 1-1.5 cm off the end of pocket. Turn off-set welt and big pocket bag onto wrong side through the given slit. Fix ends of pocket on the wrong side with double counter stitch along base-line of corners. Sew edges of pocket bags.
4. Sew and press apart shoulder and side seams.
5. Sew shoulder seams of back neck facing and front band facings. Press seams apart.
6. Pin collar right sides together, and sew outer edges from notch «0» up to top edge. Trim the seam. Snip seam allowance near marker where the seam starts. Turn collar right side out and press. Sew outer collar into the neckline of back and of front.
7. Pin front band facing to front, right sides together, and sew center front edge and lapel edge. Understitch. Sew lower edge of front band facing to front exactly along hem turnup line, leaving 1.5 cm to inner edge of the front band facing. Trim the corner. Clip seam allowance on neckline near lapel notch. Turn the front band facing onto right side, straighten seams. Sew inner collar into the neckline of facing. Press seam apart.
8. Pin left front band facing with front, right sides together, and sew left front band facing and collar. Understitch. Stitch lower edge of front band facing to front exactly along hem turnup line, leaving 1.5 cm to inner edge of the front band facing. Trim the corner. Press collar and facing. Topstitch along connecting seam of collar and neckline. Make a decorative stitch at 1 cm along the center front edge, lapel, and collar.
9. Make a pleat on lower sleeve according to mark. Sew upper and lower sleeve, right sides together. Sew sleeve seam. Sew the facing of sleeve into ring. Sew lower edge of sleeve with facing. Turn the facing onto wrong side and press hem of sleeve. Make a gathering stitch along sleeve cap for ease. Sew sleeves into armholes matching notches and adjusting ease. Sew in shoulder pads.
10. Serge and press seam allowance on hem of the garment.
11. Sew lining same as main fabric, and sew in sleeves. Turn hem of lining twice inside at 1 cm and topstitch.
12. Sew lining to inner facing edges. Sew lining to top edge of sleeve facing.
13. Fold belt in half lengthwise, right sides together, sew, leaving a an opening for turning. Turn belt right side out, and sew up opening. Make a decorative stitch along contour at 0.5 cm off the edge.
14. Make buttonholes on right front. Sew buttons according to buttonholes.

TECHNICAL DRAWING:

