

## Sewing Pattern — Dress 5077

### Recommendations on fabric:

elastic wool of 150 cm width (take into account that elastic fabric can shrink by nearly 10% after wash. Before cutting, iron the fabric through vet cloth (wrong side))

You will also need: lining of 140 cm width; zipper of 65 cm length; 2 decorative buttons

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



### **CUTTING:**

#### Fabric:

1. Middle front part – 1 folded piece
2. Side front part – 2 pieces
3. Back part – 2 pieces
4. Front yoke – 2 folded piece
5. Sleeve – 2 pieces
6. Sleeve facing – 2 pieces

#### Lining:

For front part: join paper patterns of side front/middle front parts together.  
Cut front details with darts; back part.

## **INSTRUCTIONS:**

1. Apply the fusing to wrong side of armholes, neckline, middle segments of front yokes.
2. Stitch middle back seam below zipper mark as well as front relieve/side seams.
3. Lay front yokes right sides together, stitch along the center below slit mark. Press yokes apart. Stitch outer halves of yokes to front part up to middle mark; to do this, slash middle front part's allowance at the center.
4. Stitch lining details together as follows: stitch middle back seam below slit mark, stitch darts, stitch side seams.
5. Pin the zipper to right sides of back slit's edges; pin zipper wrong side up, zipper's braid is on back part, braid's edge coincides with slit mark. Stitch the zipper along braid's middle. Pin zipper's top to slit allowances, teeth coincide slit's mark. Stitch the zipper close to teeth at 5 cm length.
6. Lay the lining on the garment right sides together, stitch the neckline. Make slashes into seam allowance at round segments.
7. Turn the lining wrong side out.
8. Stitch the zipper.
9. Stitch yokes' inner halves to lining front part up to middle front part. To do this, slash seam allowance at middle.
10. Sew shoulder seams.
11. Tack the lining and inner yokes along armholes.
12. Pin the facing and sleeves right sides together, stitch lower edges together, make 1-2 transverse stitches. Slash allowance of rounded seams, slash the seam at slit ends up to the stitch. Stitch sleeve and facing with one seam. Turn the facing into wrong side and stitch. Stitch sleeves into armholes catching facing.
13. Sew dress hem under. The lining must be 2 cm shorter than the dress.
14. Sew buttons to sleeve slits' ends.

**TECHNICAL DRAWING:**



