

Sewing Pattern — Skirt 5063

Recommendations on fabric: soft well-draping material, as viscose, as well as dense knit material

You will also need: crepe of 150 cm width; fusible interfacing; zipper; 1 button

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam Allowance: 3 cm on hem and front edge of crossover panel; 1 cm on all other seams

Attention! First of all, please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches. They must match up with corresponding pieces.



CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Darts: The fold of the dart is always pressed toward the center of your garment, or down toward the hem.

Fabric:

1. Front panel - cut 1 on fold
2. Back panel - cut 2
3. Front facing - cut 1 on fold
4. Back facing - cut 2
5. Front crossover (flying) panel - cut 1

Fusible interfacing: facings

INSTRUCTIONS:

1. Sew darts, press darts towards center.
2. Sew center back seam from zipper mark to hem. Press seam apart, including opening for zipper. Sew zipper in.
3. Serge waist, front, and lower edge of crossover panel. On fold line, turn self-facing onto right side at waist and hem, sew across. Trim corners, and turn right side out, press. Topstitch or use a decorative stitch along outer edges of crossover panel.
4. Pin crossover panel to front panel side edge. Sew side seams. Serge and press seams toward back.
5. Sew side seams of facings, press seam open, serge outer edge of facing. Sew facing to waistline of the skirt, right sides together. Careful not to catch front crossover panel. Clip into curves and understitch. Turn facing onto wrong side and tack to darts and seam allowance. Fold facing ends under and sew to zipper tape.
6. Make a buttonhole on front crossover panel, sew button to front panel correspondingly.

TECHNICAL DRAWING:

