

Sewing Pattern — Blouse 5058

Recommendations on fabric: elastic fabric (jersey)

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Middle front part – 1 piece
2. Middle back part – 1 piece
3. Side front part – 2 pieces
4. Side back part – 2 pieces
5. Sleeve – 2 pieces

INSTRUCTIONS:

1. Stitch front/back relieves. Press them toward the center.
2. Stitch shoulder/side seams.
3. Stitch sleeve seams. Stitch sleeves into armholes easing them along sleeve caps.
4. Turn in sleeve hems.
5. Turn in blouse hem.
6. Neaten neckline allowances, fold them into wrong side and pin (do not tack). Topstitch the neckline with double needle at 1 cm from the edge.
7. Make buttonholes into right front edging, make buttonholes into cuffs. Sew buttons.

TECHNICAL DRAWING:

