

Sewing Pattern — Skirt 4180

Recommendations on fabric: thin woolen fabrics of natural or mixed fibers.

You will also need: fusing; 1 button; 1 blind zipper

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: all seams -1 cm; hem of the garment - 2 cm .

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Front part – 1 folded detail
2. Back part – 2 details
3. Basque – 2 details
4. Belt – 1 detail
5. Self-belt – 1 detail

Lining:

1. Lining of front part – 1 folded detail
2. Lining of back part – 2 details
3. Lining of basque – 2 details

Fusing:

1. Belt – 1 detail

INSTRUCTIONS:

1. Apply fusing to belt.
2. Sew darts on lining. Press depths towards center. Sew middle edge of lining from zipper marker up to hem. Press apart the seam. Sew and serge side edges. Press seam allowances towards back part. Serge lower seam allowance of lining, turn inside and topstitch.
3. Sew darts on front and back panels. Press depths towards center. Serge seam allowances of middle edge of back part. Sew middle edge from zipper marker up to hem. Press apart the seam. Sew in zipper.
4. Sew side seams. Serge and press towards back part.

5. Serge lower and middle back edge of basque with lining. Turn basque onto right side and press. Make plaits and fix them on top edge. Fix upper edge of the skirt, of basque and of skirt lining.
6. Stitch belt to top edge of the skirt. Overstitch ends of the belt, slash seam allowances in corners and turn. Turn inner edge of the belt inside and topstitch into connecting seam. Press ready belt.
7. Serge lower edge of the skirt, press onto wrong side and topstitch.
8. Mark and make buttonhole (on belt). Sew on button.

TECHNICAL DRAWING:

