

## Sewing Pattern — Jacket 5057

Recommendations on fabric: wool/wool blend or crepe satin for evening wear.

You will also need: 5 large and 8 small buttons  
If the pattern has a double line around it, the seam allowances are included.

**Note:** By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam Allowance: 1 cm on all seams

Attention! First of all, please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches. They must match up with corresponding pieces.



### **CUTTING:**

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Darts: The fold of the dart is always pressed toward the center of your garment, or down toward the hem.

#### Fabric:

1. Center front – cut 2
2. Side front – cut 2
3. Center back – cut 1 on fold
4. Side back – cut 2
5. Back neck facing – cut 1
6. Collar – cut 2 on fold
7. Upper sleeve – cut 2
8. Lower sleeve – cut 2
9. Pocket facing – cut 4

#### Lining:

1. Center front – cut 2
2. Side front – cut 2
3. Center back – cut 1 on fold
4. Side back – cut 2

5. Upper sleeve – cut 2
6. Lower sleeve – cut 2
7. Pocket Sacking – cut 4

Fusible interfacing:

1. Center front – cut 2
2. Back neck facing – cut 1
3. Pocket facing – cut 4

**INSTRUCTIONS:**

1. Sew side fronts to center fronts, sew side backs to center back. Clip into curves and press seams open.
2. Make welt pockets: Fold bias pocket facings in half. Pin raw edges along pocket entrance marking and sew along markings. Cut front part between stitches, snipping diagonally toward stitch ends. Do not cut through facing! Press seam allowance flat. Turn facings to wrong side through slit to make a neat frame, then tack. Topstitch along joining seams. Turn small triangle at slit front end onto wrong side and stitch strictly to facings between upper stitch ends and lower stitch ends. Temporarily, hand-stitch folded edges of facing (welts) together. Sew lining sacking on wrong side to allowances of seams joining lower facing, sew fabric sacking to allowances of seam joining upper facing. Press sackings downward, trim sackings, adjust, and sew them together. (There are several ways to make a double welt pocket. (Here is an excellent video on an alternative way to make [Easy Double Welt Pockets](#)).
3. Sew shoulder seams, press open. Sew side seams, being careful not to catch sacking's side edges.
4. Sew upper and lower sleeves, right sides together stopping at mark for vent. Press vent's edges. On sleeve wrong side: topstitch long/upper short transverse edges of vent's one-piece facings and vent allowance. Sew small buttons to the sleeve catching vent allowance.
5. Make a gathering stitch on sleeve cap for ease. Sew sleeves in armholes, easing them along sleeve caps. Sew 4 cm width of the interfacing to joining seam allowance at sleeve caps.
6. Sew the collar along outer edges, right sides together. Clip corners, turn right side out and press. Baste collar into neckline tacking open edges together.
7. Sew lining fronts and backs the same way as garment. Sew lining's front edges to front bands, right sides together: Begin and finish stitching 8 cm before lower edge. Sew shoulder seams. Sew lining sleeve seams. Sew sleeves to armholes.
8. Lay one-piece front bands with joint lining on the jacket, right sides together and sew the neckline with front bands and the lining.
9. Turn jacket hem onto wrong side. Sew front bands to the hem.
10. Insert shoulder pads between the jacket and the lining and sew to sleeve joining seam allowances and to shoulder seam allowances.
11. Make 1 cm deep free-fitting pleats into the lining above jacket hem/sleeve hems allowance. Fold the lining under and sew to jacket/sleeve hems. Remove pins, press extra lining downward. Stitch lining seams' open segments (near front bands.)
12. Make 5 buttonholes on right front. Sew buttons on left.

**TECHNICAL DRAWING:**

