

Sewing Pattern — Trousers 5055

Recommendations on fabric: wool/semi-wool

You will also need: zipper (length depends on your size); 1 button

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Front part – 2 details
2. Back part – 2 details
3. Front sacking – 2 details
4. Back pocket – 2 details
5. Waistband – 1 detail

Additionally: 4 facings of 20 cm length and 3.5 cm width for pocket entrances

Fusing:

6. Waistband – 1 piece

Lining:

7. Front sacking – 2 pieces

INSTRUCTIONS:

1. Stitch darts, press pleats into front/back part.
2. Press reinforcement stripes to wrong side of pocket entrances. Make slit pockets into front parts: press facings along the center and topstitch them along joining lines at 0.5 cm from slits. Cut details between stitches (stop cutting before ends), cutting stitch ends diagonally. Be careful with facings and sackings when cutting! Turn facings into wrong side, turn them round edges to make neat frames. Turn small triangles at slit ends into wrong side, then topstitch on facings between ends of stitches. Stitch lining sacking to front facings' allowance, stitch fabric sacking to side facings' allowance. Stitch sackings together, then tack them to upper/side edges of front parts.
3. Stitch middle front seam below slit mark. Stitch middle back seam.
4. Press closure's right one-piece facing and slit's left edge into wrong side. Tack zipper's braid to slit left edge, with its teeth close to bending. Fold slit allowance along the center and process neatly one of short edges (= closure allowance). Neaten open lengthwise edges together. Tack slit allowance under slit's left edge so that it projected by 3 cm. Topstitch closure's left edge along the edge catching zipper braid and slit allowance. Pin slit edges together. Stitch zipper's free braid to right facing. Do not catch garment right part's fabric! Topstitch right part along marks catching facing and slit allowance (at lower part).
5. Stitch side/inside leg seams.
6. Stitch back seam; stitch one of waistband's lengthwise edges to garment's upper part (right side); stitch closure's allowance to upper part of slit allowance. Fold the waistband along the center and stitch along short edges. Press half of waistband into wrong side, fold lower edge under and pin it to joining seam. For coulisse: topstitch the waistband along both edges of joining seam between darts. Cut elastic braid into 2 pieces; insert pieces into the coulisse and stitch to waistband continuing each dart's line. The distance between darts must now be 19,5/20,5/21,5/23/24,5/26 cm. Stitch open lower edge along joining seam. Topstitch the waistband along coulisses' centers between crosswise stitches, stretching elastic braids. Make a buttonhole at 1 cm from waistband's short edge.
7. Press one-piece facings of pocket upper edges into wrong side, fold it under and topstitch at 1.5 cm distance. Pin pockets to back parts and topstitch along edges.
8. Sew hems.

TECHNICAL DRAWING:

