

## Sewing Pattern — Coaldress 5047

Recommendations on fabric: wool/semiwool (+satin for lapels and the collar for evening variant)

You will also need: 8 large buttons and 6 small buttons; lining; fusing

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



### **CUTTING:**

#### Fabric:

1. Middle front part – 2 details
2. Side front part – 2 details
3. Back part – 2 details
4. Collar – 2 details
5. Sleeve – 2 details
6. Front band – 2 details

#### Lining:

1. Front part – 2 details
2. Back part – 2 details
3. Sacking – 2 details

#### Fusing:

1. Front band – 2 details
2. Collar – 1 detail

## **INSTRUCTIONS:**

1. Stitch the sacking on middle front part right sides together between pocket entrance markings. Slash middle front part's seam allowance up to stitches' ends. Fold the sacking into wrong side, press pocket entrance. Slash allowance near the dart and make transverse seam into front parts. Stitch sackings together on wrong side. Stitch front relieve and stitch little dart with the same seam.
2. Stitch middle back seam, stitch darts, stitch side/shoulder seams.
3. Stitch darts/middle back seam/side seams into lining details.
4. Stitch front bands to lining front part. Stitch shoulder seams.
5. Stitch inner collar into neckline up to the mark; stitch outer collar to front bands/lining: to do it, slash allowances to neckline corner. Press seam allowances apart. Lay outer collar and front band on the garment right sides together. Stitch front edgings/lapels/collar's outer sides up to the marking. Turn the collar right side out, fold front edges into wrong side. Stitch collar joining seam's allowance between shoulder seams from inside.
6. Tack the lining to armholes. Turn in the dress and the lining.
7. Sew front bands to hem allowance.
8. Stitch sleeve darts. Stitch sleeve seams. Turn sleeves in and stitch them into armholes catching the lining.
9. Make 4 buttonholes into right front edging. Make upper buttonhole into left front edging to inner flat button. Sew buttons on both front edgings and on sleeves. When sewing upper button to right front edging, catch flat button from wrong side; catch the dart on sleeves when sewing buttons.
10. Fold lapels as marked into right side, press bending line a little.

**TECHNICAL DRAWING:**

