

## Sewing Pattern — Waistcoat 5045

Recommendations on fabric: soft wool/lace fabric (evening variant)

You will also need: lining; fusing; 7 buttons

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



### **CUTTING:**

#### Fabric:

1. Middle front part – 2 details
2. Side front part – 2 details
3. Front yoke – 2 details
4. Middle back part – 1 folded detail
5. Side back part – 2 details
6. Back neckline facing – 1 detail

#### Lining:

1. Middle front part – 2 details
2. Side front part – 2 details
3. Front yoke – 2 details
4. Middle back part – 1 folded detail
5. Side back part – 2 details
6. Sacking – 4 details

#### Fusing:

1. Yoke front band – 2 details
2. Front band – 2 details
3. Back neckline facing – 1 detail

## **INSTRUCTIONS:**

1. Stitch front relieves excluding pocket entrances.
2. Stitch sacking to pocket entrances wrong side as marked. Fold sacking front ward and stitch together.
3. Stitch back darts and relieves.
4. Stitch yokes to front parts. Stitch shoulder seams.
5. Stitch front relieves into lining details. Stitch yokes to front parts. Stitch back darts and relieves. Stitch lining front parts/yokes to one-piece front bands. Stitch back neckline facing to back lining.
6. Stitch shoulder seams.
7. Lay the lining with back neckline facing on the waistcoat right sides together and overstitch the neckline neatly. Stitch the lining to armhole edges. Cut seam allowance close to the stitch. Turn the waistcoat right side out. Topstitch the lining on seam allowances close to the seam.
8. Stitch side seams of fabric/lining waistcoat with the same stitch.
9. Turn the waistcoat in. Sew front bands to hem allowance. Pin pleats of 2 cm depth above lining side seams. Fold the lining under and sew it to waistcoat hem allowance rounding it upward to one-piece front bands. Remove pins and press extra facing downward.
10. Make buttonholes into right front edging and sew buttons to left one.

**TECHNICAL DRAWING:**

