

Sewing Pattern — Jacket 5043

Recommendations on fabric: wool/artificial leather

You will also need: fusing; lining; 1 long separable zipper and 4 short zippers

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Middle front part – 2 details
2. Side front part – 2 details
3. Middle back part – 2 details
4. Side back part – 2 details
5. Back neckline facing – 1 detail
6. Upper sleeve – 2 details
7. Lower sleeve – 2 details
8. Front band – 2 details

Lining:

1. Front part – 2 details
2. Back part – 2 details
3. Upper sleeve – 2 details
4. Lower sleeve – 2 details
5. Sacking – 4 details

Fusing:

1. Front band – 2 details
2. Back neckline facing – 1 detail

INSTRUCTIONS:

1. Stitch front relieves and darts.
2. Lay sacking on front part right sides together along marked pocket entrance line, then stitch as marked. Cut front part between stitches diagonally toward stitches' beginning. Do not cut through seams! Press seam allowances apart. Fold sackings into wrong side through the slit rounding seam allowances, then tack. Fold small triangles at slit ends into wrong side. Lay the zipper into pocket slit and tack. Make decorative stitch along frame edge at 0.5 cm stitching the zipper at the same time. Stitch sacking seam catching allowance's corners.
3. Stitch back relieves/side/shoulder seams. When stitching side seams, do not catch sacking's side edges.
4. Stitch sleeve seams. Leave a slit of zipper length into outside sleeve seam. Insert the zipper into sleeve seam (wrong side), then tack. Make decorative stitch along slit edge at 0.5 cm distance stitching the zipper. Turn in the sleeve.
5. Stitch sleeves in easing them along sleeve caps.
6. Stitch neckline facing to front bands' upper edges. Lay front bands on front parts right sides together, insert the zipper with its teeth inside, overstretch front endings/necklines with front bands and facings. Fold front bands/facings into wrong side, press edges.
7. Stitch lining details together. Stitch lining front edges to front bands right sides together; begin/finish the seam 8 cm before lower edge. Pull the lining into the jacket wrong sides together. Fold lining open edges under and sew to fabric jacket/sleeve hems. Sew lining's front open edges to front bands.

TECHNICAL DRAWING:

