

Sewing Pattern — Skirt 5041

Recommendations on fabric: well-draping material, for example, viscose, crepe, and dense knit fabric

You will also need: crepe of 150 cm width; zipper.

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Front panel -2 details
2. Back panel - 2 details
3. Front facing - 1 folded detail
4. Back facing - 2 details

Clue interfacing: facings

INSTRUCTIONS:

1. Sew darts and press them towards center.
2. Sew front center seam up to slit mark. Press seam allowance apart, press slit allowance to the left side.
3. Sew back center seam up to zipper mark.
4. Sew side seams.
5. Sew zipper so that teeth are covered on both sides.

6. Turn over hem allowance along hemline, press. Face corners “in envelope.” Topstitch the front center seam. Continue to topstitch along slit edges and hem at 3 cm distance with a double needle.

7. Sew facing side seams. Sew facings and waistband right sides together. Cut closely seam allowance closely to stitches, turn to topstitch and topstitch to edge. Turn facing to left side and sew it to dart depths and seam allowance. Turn under facing edges and sew to zipper band.

TECHNICAL DRAWING:

