

Sewing Pattern — Trousers 5038

Recommendations on fabric: soft well-dapped fabric

You will also need: zipper (length depends on your size); 1 button

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

- 1. Front part 2 details
- 2. Back part 2 details
- 3. Waistband 1 detail

INSTRUCTIONS:

- 1. Stitch darts, press darts' depths towards the center.
- 2. Stitch side seams, leave unstitched segment into left upper seam. Stitch inside leg seams, press seam allowances apart. Stitch middle front/back seams with one stitch. Press seam allowances between top and roundings apart.
- 3. Press slit allowances into wrong side. Stitch the zipper under slit edges.
- 4. Fold the waistband along the center, stitch short edges. Lay outer waistband on the garment right sides together, stitch it to trousers' upper edge. Fold inner waistband under and sew it to joining seam. Sew hooks.
- 5. Fold hems into wrong side and sew.



TECHNICAL DRAWING:



