

Sewing Pattern — Skirt 5027

Recommendations on fabric: soft cloth, wool crepe, gabardine of 150 cm width.

You will also need: zipper; 1 button; fusing.

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Waistband - 1 detail
2. Back panel - 2 details
3. Middle part of front panel - 1 detail
4. Side part of front panel - 2 details
5. Belt loop - 1 detail

Fusing: strengthen the waistband with fusing.

INSTRUCTIONS:

1. Sew darts into back panels and press towards center.
2. Sew back center seam between zipper and slit marks, sew side seams. Sew zipper in.
3. Press slit allowance to wrong side, and topstitch it.
4. Sew waistband to waistline edge right wide on left leaving closure allowance on right back end. Sew ends. Fold under the seam allowance of the open waistband edge overlapping the joining seam and topstitch closely along the edge. Work a button hole into the left end of the waistband and sew button to the right end.
5. Fold under allowances of vent long sides and topstitch the vent along the edge on long sides. Cut the detail into pieces. Fold the belt loops under and topstitch on the waistband.

6. Turn over hem allowance along hemline, press, then topstitch.

TECHNICAL DRAWING:

