

Sewing Pattern — Skirt 5026

Recommendations on fabric: soft wool, gabardine of 150 cm width

You will also need: 3 zippers; fusing

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Front panel facing - 1 detail
2. Back panel facing - 2 details
3. Front panel - 1 detail
4. Side part of front panel - 2 details
5. Back panel - 2 details
6. Strengthenener - 2 details

Fusing: strengthen facings with fusing.

INSTRUCTIONS:

1. Sew darts into back panel and press them towards center.
2. Turn zipper allowance of front panel and front panel side part into wrong side. Insert the zipper between zipper allowance with its teeth open and tack. Underlay the strengthener under zipper and topstitch the zipper from right side.
3. Sew front center seam from the zipper mark down to slit. Sew zipper in.
4. Press slit allowance into wrong side and topstitch.
5. Sew side seams.

6. Sew side facing edges. Face facings and skirt waistline right sides together, then work. Fold facing into wrong side, tack open edge. Fold front center seam of facing under and sew it to zipper band.
7. Topstitch joining seams of skirt sides on 0.5 cm distance.
8. Turn over hem allowance, press and topstitch.

TECHNICAL DRAWING:

