

Sewing Pattern — Skirt 5025

Recommendations on fabric: moreen (cotton fabric)

You will also need: lining; 1 zipper; 1 button

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Front middle panel – 1 folded detail
2. Back panel – 2 details
3. Front upper side – 2 details
4. Front lower side – 2 details
5. Waistband

Lining:

6. Pocket lining upper part – 2 details
7. Pocket lining lower part – 2 details

INSTRUCTIONS:

1. Sew back darts, press them towards the center.
2. Neaten pockets. Sew side parts to middle one of front panel.
3. Sew back middle seam between notch marks for closure and vent. Sew side seams. Sew the zipper in.

4. Fold the waistband along the center, sew short sides and closure allowance. Sew waistband outer part to garment upper part right sides together. Fold waistband inner part under and sew it to joining seam. Stitch the waistband along the edges. Make a buttonhole.

5. Neaten the hem. Press vent one-piece facing (back left panel) to wrong side along the bending line, and sew to hem. Sew vent allowance lengthwise edge (back right panel) as narrow as possible. Topstitch back left panel at the vent top diagonally upward catching vent allowance.

TECHNICAL DRAWING:

