

Sewing Pattern — Jacket 5018

Recommendations on fabric: wool, wool blend

You will also need: fusible interfacing; 3 buttons; lining

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam Allowance: hem 3 cm; all other seams 1 cm

Attention! First of all, please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches. They must match up with corresponding pieces.



CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Darts: The fold of the dart is always pressed toward the center of your garment, or down toward the hem.

Fabric:

1. Upper pocket frame – cut 2
2. Lower pocket frame – cut 4
3. Collar – cut 2
4. Back – cut 2
5. Back neck facing – cut 1
6. Front – cut 2
7. Front band facing – cut 2
8. Upper sleeve – cut 2
9. Lower sleeve – cut 2

Lining:

10. Upper sleeve – cut 2
11. Lower sleeve – cut 2
12. Back – cut 2
13. Front – cut 2
14. Upper pocket upper sacking – cut 2

15. Upper pocket lower sacking – cut 2
16. Lower pocket upper sacking – cut 2
17. Lower pocket lower sacking - cut 2

Fusible interfacing: apply the interfacing to wrong side of front band facings. Back neck facing, front.

INSTRUCTIONS:

1. Sew front/back darts, press toward center.
2. Cut front slit pockets “in frames”: apply a strip of fusing 4 cm width to wrong side of pocket marking. Lay 2 pocket facings on front, pin them right sides together along pocket entrance marking and stitch. Lengthwise edges of facings match up to pocket marking middle line. Snip the front part between stitches, then snip diagonally toward stitch ends. Do not cut facings! Press seam facing allowances apart. Fold facings onto wrong side through the slit to make a neat frame, then tack. Lay sacking on front wrong side, on lower facing (lay sacking upward); topstitch lower facing on right side along joining seam catching the sacking. Press sacking downwards. Fold the allowance of one of valance long edges and topstitch the valance on another sacking. Lay another sacking on the pocket on front wrong side and stitch it on right side seam joining upper facing. Turn small triangles at slit ends onto wrong side and topstitch accurately between upper stitch ends and lower stitch ends. Trim sackings, adjust, and sew them together. Here is a great tutorial on the double welt pocket: [Double Welt Pocket](#) and to assist with the upper pocket: [Single Welt Pocket](#).
3. Sew shoulder/side seams. Press seams open.
4. Pin front band facing to center front edges, right side together, and sew. Sew lower edge of band facing along hemline. Sew shoulder seams of front band facing to back neck facing.
5. Pin collar, right sides together, and sew outer edges. Clip into curves and turn right side out. Sew inner collar to garment neckline; sew outer collar to facing neckline. Press seam allowance apart. Sew pressed allowance of inner collar joining seams and back neckline facing from inside.
6. Serge lower edge of garment, turn onto wrong side, and hem by hand or topstitch.
7. Make a gathering stitch along sleeve cap for ease. Sew sleeves into garment armholes matching notches and adjusting ease.
8. Sew in shoulder pads.
9. Sew darts on lining front/back. Sew lining together same as main fabric. Sew lining to sleeve lower edges, and to inner edges of front band/neck facing. Hem lining shorter than garment hem.
10. Make buttonholes on right front, sew buttons on left.

TECHNICAL DRAWING:

