

## Sewing Pattern — Coat 4176

Recommendations on fabric: fabric suitable for coats.

You will also need: fusible interfacing, 6 buttons, lining, shoulder pads.

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Seam allowance: 1 cm on all edges. Seam allowance on hem of the garment and of sleeve 2 cm, along edges of pocket bags and off-set welt — 2 cm.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches, they must coincide.



### **CUTTING:**

(On the pattern pieces, “beam” means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.)

#### Fabric:

1. Upper back – cut 2
2. Lower back – cut 2
3. Side back – cut 2
4. Yoke – cut 1
5. Facing of yoke – cut 1
6. Center front – cut 2
7. Side front – cut 2
8. Facing/buttonstand – cut 2
9. Upper sleeve – cut 2
10. Lower sleeve – cut 2
11. Back neckline facing – cut 1
12. Upper collar – cut 1
13. Lower collar – cut 1
14. Off-set welt – cut 2
15. Button band of sleeve – cut 2
16. Belt – cut 1
17. ruffle 1 – cut 1
18. ruffle 2 – cut 1
19. ruffle 3 – cut 1

20. ruffle 4 – cut 1
21. Belt loop — cut 1

Lining:

1. Side back – cut 2
2. Side front – cut 2
3. Upper sleeve – cut 2
4. Lower sleeve – cut 2
5. Lining of back – cut 2
6. Center front – cut 2
7. Big pocket bag – cut 2
8. Small pocket bag – cut 2

Fusible Interfacing:

facing/button-stand, back neckline facing, top collar.

Attention: Details of lining of front and of back are cut using patterns for main fabric except for the width of button-stands and facings correspondingly.

**INSTRUCTIONS:**

Attention: Front side edges, back side edges and side edges of the garment are serged from waist to hem before sewing them together.

1. Apply fusing to facing/button-stand, back neckline facing, top collar, edge of the armhole on front and on back. Apply interfacing to place for pocket on side front. Apply stitched bias tape from fusing 1 cm wide along fold line of lapel on front.
2. Mark place of pocket. Press off-set welt in half lengthwise wrong sides together. Topstitch small pocket bag on inner side of off-set welt. Sew off-set welt to front part along lower marking line of pocket. Sew big pocket bag to front part along top marking line of pocket. Stop stitching near short marking lines. Cut entrance into pocket. Make slope slashes 1-1.5 cm off the end of pocket. Turn off-set welt and big pocket bag onto wrong side through the resulting slit. Tack ends of pocket from the wrong side with double back stitch along the corners. Sew edges of pocket bags. seams.
3. Sew side fronts to center fronts. Press open seam.
4. Sew center back seam. Press open seams.
5. Stitch lower edge of yolk and yolk facing. Trim seam. Turn the facing to wrong side, press and Topstitch on 0.5 cm off the edge. Place yoke on top part of back and topstitch along yoke with decorative/fixing stitch.
6. Serge lower and top edges of ruffle 2, ruffle 3 and ruffle 4. Serge lower edge of ruffle 1. Turn under lower edges of ruffles and topstitch. Place ruffle 4 on lower back right sides together. The lower edge of the ruffle is turned upwards. Topstitch the ruffle according to markers. Turn the ruffle downwards and baste to back along side edges. In the same way topstitch ruffle 2 and ruffle 3. Baste ruffle 1 to lower back part along top and side edge.
7. Sew center back and lower back together. Press the seam upwards. Sew side backs to center back. Press seam allowances to side edge.
8. Sew and press open shoulder and side seams.
9. Stitch back neckline facing to buttonstands, press open seam allowances.
10. Put together collars right sides together and topstitch outer edge and ends of collar. clip into seam allowances near notches, turn collar right side out and press.
11. Serge and press hem of the garment. Put facing/buttonstand onto right side of front right side downwards, pin together and stitch along facing/buttonstand and hem exactly along the marked line. Stitch upwards to the notch, marking the end of sewing in collar. trim seams of top and lower

- corners of facing/buttonstand. Topstitch seam allowance of facing/buttonstand: on closure part – onto facing/buttonstand, on lapels part – onto facing/buttonstand of front part. Stitch by 0, 2 cm off the seam. Turn buttonstands onto right side, straighten seams. Topstitch hem of the garment.
12. Sew in lower collar into the neckline of coat, and top collar into the edge of neckline facings of back and facings/buttonstands. Press open seams. Fix together seams of sewing in top and lower collars. Turn garment onto right side, press.
  13. Serge belt loop on one long side. Press seam allowances on belt loop and topstitch (serged seam allowance is on top). Cut into belt loops.
  14. Topstitch belt loops onto sleeve end at marks. Sew and press open elbow seam of sleeve. Press hem of sleeve. Sew and press open front seam of sleeve.
  15. Sew sleeves into armholes according to notches. Sew in shoulder pads.
  16. Sew seams of sleeve lining and baste to inside at armhole. Turn hem to inside by 1 cm two times and topstitch.
  17. Stitch lining to inner facing/buttonstand edges and neckline facing of back. slipstitch lining to sleeve lining at armhole.
  18. Put decorative stitching line along facing/buttonstand and collar.
  19. Fold button band of sleeve in half lengthwise right sides together. Sew together, leaving an opening for turning. Turn button band right side out through opening. Press, and slip-stitch opening. Put decorative stitching line along edge by 0.5 cm off the edge.
  20. Fold belt in half lengthwise right sides together and sew together, leaving an opening in the middle for turning. Turn belt right side out and slip-stitch opening. Put decorative stitching line along contour 0.5 cm off the edge.
  21. Sew belt loops at seams of side fronts and side backs.
  22. Make buttonholes into right front and sleeve button bands. Sew on buttons accordingly. Sew a decorative button onto yoke.

### **TECHNICAL DRAWING:**

