

Sewing Pattern — Coat 4175

Recommendations on fabric: coat fabrics of natural or mixed fibers

You will also need: fusing; lining; shoulder pads; sleeve heads; 8 buttons.

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Seam allowance: all seams - 1 cm; on hem of the garment - 4.5 cm

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.

ATTENTION! Legend on patterns is made on right side



CUTTING:

Fabric:

1. Central back part – 2 details
2. Side back part – 2 details
3. Side upper part of front part – 2 details
4. Side lower part of front part – 2 details
5. Central front part – 2 details
6. Lapel – 4 details
7. Upper collar – 1 detail
8. Lower collar – 1 detail
9. Buttonstand – 2 details
10. Back neckline facing – 1 detail
11. Upper sleeve part – 2 details
12. Lower sleeve part – 2 details
13. Cuff – 2 details
14. Flap – 2 details
15. Belt – 1 detail
16. Belt loop – 1 detail

Lining:

1. Central back part – 2 details
2. Side back part – 2 details

3. Side front part – 2 details
4. Upper sleeve part – 2 details
5. Lower sleeve part – 2 details
6. Flap – 2 details
7. Pocket bag – 4 details

ATTENTION: details of back part from lining are cut except for the width of neckline facings of back part

Fusing: buttonstand, back part neckline facing, central front part, flap, lapel, top collar

INSTRUCTIONS:

Attention: put decorative stitch along seams and along the flaps perimeter on 0.8 cm off the edge. Side and relieve edges are serged from waist up to hem.

1. Apply fusing to details.
2. Overstitch flap with lining. Slash seams on rounded parts, turn details out and press. Put decorative stitch.
3. Overstitch upper edge of lower side front part with pocket bag exactly between markers, leveling markers on pocket bag with round markers on front part. Turn pocket bag onto wrong side and press. Put flap onto side top part of front part right sides together, put pocket bag from above. Stitch details exactly between markers. Turn flap downwards, press seam upwards. Place upper and bottom front parts edge-to-edge and fix with temporary stitch. Sew and serge edges of pocket bags.
4. Sew relieve edge on front part, turning pocket bag. Press seam towards center and stitch.
5. Sew and press relieve edges to middle seam of back part. Stitch. Sew and press apart middle seam of back part. Sew and press apart shoulder seams. Sew and press side seams to back part.
6. Sew and press apart shoulder edges of back part neckline and buttonstands facings.
7. Fold lapels pairwise right sides together and overstitch on outer edge. Slash seam allowances, turn details out and press. Stitch.
8. Make and fasten soft plaits on top collar. Fold collars right sides together and overstitch ends and outer edge of collar. Turn details out, press and stitch.
9. Put additional fusing along front part neckline edge. Stitch lapels to neckline. Sew collar into the neckline. Put buttonstand with facing onto right side of front part right side downwards, pin together and overstitch buttonstand, the neckline of front part and the neckline of back part. Overstitch from front part side. Topstitch seam allowance of buttonstand on closure section on buttonstand. Stitch by 0, 2 cm off the seam. Stitch lower edge of buttonstand to front part exactly on marked line of hem turning, leaving 1.5 cm to inner edge of buttonstand. Turn buttonstands onto right side, straighten seams.
10. Make and fasten soft plaits on lower part of sleeve. Sew sleeve seam up to notches. Slash seam near marker and press apart. Overstitch lining lower part of sleeve the same way. Overstitch slit on sleeve with lining. Level and fix lower edges of sleeve and lining.
11. Fold cuff in half lengthwise and overstitch side sides and sections up to notches. Slash seam allowance near notches, turn details out and press. Stitch outer edge of cuff to sleeve, turn inner edge of cuff inside and topstitch into the seam. Put decorative stitch along the perimeter of cuff.
12. Sew and press apart top part of sleeve seam. Sew sleeves into armholes according to notches. Stitch shoulder pads and sleeve heads.
13. Sew seams on lining details and sew in sleeves. Turn seam allowance of lower edge of lining twice on 1.5 cm and topstitch.
14. Serge and press seam allowance onto hem of the garment. Stitch lining to inner buttonstand edges and neckline facing of back part. Start and finish the stitch on half of hem turning width of main garment. Slash seam allowance on inner edge of buttonstands near beginning of lining connection. Turn seam allowance of buttonstand from hem line up to the notch inside and undersew with invisible stitches. Serge the seam of lining and press towards side of lining.
15. Stitch lower part of sleeve to top, inserting lower part and lining between top and lining of top part of sleeve. Turn details out. Press seam upwards and topstitch.

16. Put decorative stitch along buttonstand.
17. Serge buttonholes on right front part, sew buttons on left front part.
18. Fold detail of the belt in half lengthwise right sides together and overstretch on three sides, leaving a slit on long edge for turning out. Turn belt onto right side, turn seam allowances of unsewn section inside and put decorative stitch along the perimeter of the belt.
19. Serge one longitudinal edge on belt loop detail. Press unsewn edge inside, closing with serged edge from above. Put double stitch, fixing longitudinal seam allowances. Cut belt loop into 2 parts. Stitch belt loops on side seam level. Run the belt.

TECHNICAL DRAWING:

