

Sewing Pattern — Skirt 4174

Recommendations on fabric: costume fabric.

You will also need: fusing, lining, invisible zipper.

Seam allowances are provided if the pattern has double contour.

Seam allowances are NOT included if the pattern has single contour and need to be added when laying out and cutting details.

Seam allowance on hem – 2 cm, all other seams - 1 cm.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count double and symmetrical details.

When sewing the garment, pay attention to notches, they must coincide.

CUTTING:

Main fabric:

1. Front part – 1 detail
2. Back part – 1 detail
3. Side top part – 1 detail
4. Front facing – 1 detail
5. Back facing – 1 detail

Lining:

1. Lining of front part – 1 detail
2. Lining of back part – 1 detail

Fusing:

1. Front facing – 1 detail
2. Back facing – 1 detail

INSTRUCTIONS:

1. Apply fusing to facings.
2. Slash corner on pattern for front part as marked by notches. Make lower plait. Stitch top side detail to front part. Slash seam allowance in corner and serge.
3. Make top plait and fix along top edge.
4. Serge side edges. Sew right side edge, press seam allowances apart. Sew left side edge from marker downwards. Press seam allowance apart. Sew in zipper.
5. Sew right side edge of the facings. Press seam allowance apart. Serge and sew side edges of lining like details from main fabric. Make plaits on lining of back part. Stitch the facing to lining. Press seam allowance downwards. Stitch facings to upper edges of the skirt. Turn seam allowance on the facing and topstitch by 0.2 off the seam. Undersew side edges of facings and of lining to zipper.
6. Turn the seam allowance of hem of lining inside twice by 1 cm and topstitch. Serge seam allowance of the hem of the skirt, turn inside, press and undersew with invisible stitches.



TECHNICAL DRAWING:

